The Hong Kong Cricket Club is 155 years old and is one of the oldest cricket clubs in the world. It is also used for lawn tennis, croquet, football, netball and general recreation. Curator, Ricky Aitken, relates the re-construction of the ground undertaken last year...

The challenge of working in Hong Kong as a Cricket Curator has proved to be both challenging and rewarding. The club site has an annual rainful of around 3,000mm. The temperatures are extremely variable – during th winter monts they can be as low as 6 degrees with no rainfull, and summer temperatures can be as high as 36 degrees, with rainfall as high as one metre in a month. Tuff managemement skills need to be finely tuned. The cricket ground is a unique set up where one corner is taken up by a lawn bowling green and another

12 Golf and Sports Turf Australia July/August 2006

ruken up by an artificial tennis court, which are both utilized during non cricker mach times. In the winter of 2004, the committee of the Hong Kong Cricket Club unanimously agreed that the time was right to upgrade the cricket ground with a full reconstruction. The current location, in the highlands of Hong Kong, has been the clubs home for the past 30 years. It was relocated from a possible location in the heart.

popular location in the heart popular location in the heart of the city. During the relocation in the 1970s, the Hong Kong Government prepared a site, by filling a valley in-between two mountains. The fill used for the site was poor quality, causing turf management to be difficult. The associated problems with the existing ground were poor turf selection and quality, lack of drainage, poor performing growing medium, excess black layer, uneven surface falls, localized undulations and poor performing

irrigation system.

When the planning process began, consideration revolved around the difficult climatic conditions, along with the type of construction that would be

localized undulations and poor performing

suit the clubs needs. Consideration was given to a full USGA construction, however it was decided that a modified Californian-type construction was more suited to our needs. The growing medium, the drainage, and the turf species were considered the three most important factors in the reconstruction, in order for the ground to be able to deal with the conditions and high usage from

During the relocation in the 1970s, the Hong Kong Government prepared a site, by filling a valley in-between two mountains

members. Determining the best selection of turf species was not an easy choice. Thought was given to a whole range of warm season grasses. After much deliberation, Season Paspalum was selected because of its ability to handle both warm and cool season temperatures; short dormancy during coldest period of the year; ability to recov from wear; ability to handle long periods of low light intensity, and its ability to present as well as any cool season grass.

RENOVATION SUCCESSES

continued > continued > A southern China nursery was contracted to grow the turf, where we made regular inspections to ensure a reasonable standard of turf

reasonable standard of turf
was reached.
We also looked at the
growing medium. A
Brishane-based company,
Greenway Solutions, was
employed to provide technical
support in developing an ideal
growing medium. We were looking to
create a high-quality growing medium that could cope with the Hong
Kong rainfall, but also wanted to create a medium that provided the
chemical and biological characteristics of a natural soil. It was decided
to create a custom blend to be mixed off-site and it was obvious that the
base of the medium would have

off-site and it was obvious that the base of the medium would have to be sand that met the USGA standard. Three main products were incorporated with the sand to make up the final growing medium. The first was Profile Greens, a ceramic product that u lilite clay and amorphous Silica as its base mineral. It has a very high Carlion exchange capacity. high Cation exchange capacity, a particle size that meets USGA specification and is a very similar





product to Zeolite. It was used so the pore space of the sand wa product to Zeolite. It was used so the pore space of the sand was blanned, causing that percolation of the final root zone mix would not be reduced after incorporating the other two amendments. This was incorporated into the sand at a rate of 10% file second product was Environganics, a fully composted organic fertilizer that uses cattle manure as its organic source. This was incorporated into the sand at a rate of 59%. The third product added was Humatte, a readily available carbon source that boasts



RENOVATION SUCCESSSES W

a 70% Humic Acid content. This was incorporated into the sand at a rate of 196. Both Envirorganics and Humate were added to the sand in order to create microbe food sources to stimulate essential microbial activity and soll biological cycles for a healthy a root zone environment. The three amendment products made up 16% of the final root growing medium mix and were incorporated three times through a mixing plant off-site, which eventually made up the

humongous growing medium.

It's not unusual to receive a metre of rain It's not unusual to receive a metre of rain within a calendar month, so drainage was an important factor. A drainage rate of 25mm of rainfall per hour was set as the drainage design rate. In order to put in place a drainage system to cope with 25mm of rainfall per hour. Hooghoudt's formula was used, taking into consideration the soil profile depth, the drainage pipe spacing, and the infiltration rate of the

growing medium that would be used. The calculation told us that we needed to construct a that we needed to construct a soil profile to a depth of 250mm using a drainage pipe spacing of 3 metres. The next phase of the planning process was to identify irrigation system. A maintenance friendly Rain Bird system using 7005 heads was chosen because of their case of adjustment and lasting qualities. After being put out to tender, Asian Shortstruct Consultants

After being put out to tender,
Asian Sportsturf Consultants
were awarded the contract as
the committee had the full
confidence that ASC had the
skills and resources to carry out
the project with the necessary
degree of accuracy.
The contract period was 12
weeks and commenced at the end of March
2050: There was approximately
2,200m* of soil excavated from
the site to make way for the ne-

2,200m³ of soil excavated from the site to make way for the new ground. The sub-base was graded with a laser operated grader to achieve the 198 call from the centre pitch area to the boundary as per the specification. The drainage was 'cut in' to the compacted sub-base using a trenching machine at 3 meter spacing, using a half herringbone drainage design. The lateral drainase noise used were herringbone drainage design. The lateral drainage pless used were 100mm ADS perforated pipe and the lateral pipes were connected into a 200mm ADS perforated pipe that acted as a catcher drain for the lateral pipes that surrounded the edge of the ground. All trenches and pipes carried a fall of 1½%, and and pipes carried a fall of 1½%, and all trenches were backfilled with 5-7mm washed aggregate. Due to the nature of fold sub-base soil, there were many difficulties during there were many difficulties during



the trenching process, with rocks needing to the trenching process, with rocks needing to be 'jack hammered' out of the drainage lines. The installation of the irrigation system was incorporated at the same time as the drainage

incorporated at the same time as the draina system, but in separate trenches.

On completion of the drainage and irrigation system, the pre-mixed root zone was transported in from the mixing site and spread in two layers of 125mm.

It was consolidated at the conclusion of It was consolidated at the conclusion of each layer with lightweight machinery and heavy irrigation to avoid any movement or disruption to surface levels at a later date. Once the entire growing medium was in place, the final levels were obtained using a laser level to mirror the sub-base levels, which is a 1% fall from the cricket square to the boundary. The turff was laid over a period of 5 days – the turf was lightly rolled upon completion and received its first cut within 5 days of being laid. The ground was open within four weeks of completion.

The project was completed 10 days under the contract period. In the mouth that followed, there was 900mm of rainfall which posed no problems for the drainage system.

